

BASIC DESCRIPTION

JETSEAL is a premium filled asphalt emulsion sealer for asphalt pavement that protects against the damage caused by occasional oil and gas spills, and the effects of winter freeze/thaw cycles. JETSEAL is used to restore a rich black appearance making old pavement look like new.

PHYSICAL PROPERTIES

Color	- Black
Solids	- 40%
Dry to Touch	- 2 - 8 hours (depending on temperature and humidity)
Ready for Traffic	- 24 hours
Coverage	- 75-150 square feet per gallon

LIMITATIONS

Do not allow product to freeze. JETSEAL is water soluble prior to curing consequently newly applied material must be protected against frost or rain. Minimum application temperature is 41⁰F. (5⁰ C).

JETSEAL is not resistant to prolonged exposure to oil and gas.

PREPARATORY WORK

New pavement must be allowed to cure so that water does not bead on the pavement surface. Clean area to be sealed. Fill potholes with Innovative Mfg. Inc. Instant Asphalt Patch #2103 and allow to cure. Seal all cracks with Innovative Mfg. Inc. Rubberized Crack Seal #2104 and allow to set. Mix JETSEAL before use. Apply by squeegee or broom. Maintain uniform parallel strokes. Clean up with water before product has cured, otherwise use solvent (#1707 Resolve).

PACKAGING

Available in 16 ltr. plastic pails and 205 ltr. drums .

Note

As the manufacturer does not have control of the application process and conditions, liability is limited to the replacement of proven defective product.